

1	900.005	EXTERNAL FEEDING BASE "NOT" LOGICAL ELEMENT
2	900.18.0	SWITCH PROTECTION
3	900.18.1-1	PRESSURE SWITCH 1 bar, THR. CONN.
4	900.18.1-4	PRESSURE SWITCH 4 bar, THR. CONN.
5	900.18.1/1-1	PRESSURE SWITCH 1 bar, FASTON CONN.
6	900.18.1/1-4	PRESSURE SWITCH 4 bar, FASTON CONN.
7	900.18.2N	IMPULSES GENERATOR
8	900.18.3	PNEUM. TIMER N.C. 30 s.
9	900.18.3.60	PNEUM. TIMER N.C. 60 s.
10	900.18.4	PNEUM. TIMER N.O. 30 s.
11	900.18.4.60	PNEUM. TIMER N.O. 60 s.
12	900.18.9	TWO HANDS SAFETY VALVE: III A CLASS CERTIFICATION according to EN 574 standard)
13	900.18.10	TWO HANDS SAFETY VALVE: III B CLASS CERTIFICATION according to EN 574 standard)
14	900.18.11	TWO HANDS SAFETY VALVE: ADAPTER FOR POWER VALVE
15	900.52.1.1	TWO HANDS SAFETY VALVE
16	900.52.1.2	FLIP-FLOP VALVE
17	900.52.1.3	FLIP-FLOP VALVE - PNEUMATIC VERSION (see technical specifications n° 013/900)
18	900.52.1.4	FLIP-FLOP VALVE - ELECTRIC VERSION with M2 (see technical specifications n° 014/900)
19	900.52.1.5	FLIP-FLOP VALVE - ELECTRIC VERSION with M3P (see technical specifications n° 015/900)
20	900.52.5	OSCILLATOR VALVE 1/8" - 5/2
21	900.52.5C	OSCILLATOR VALVE 5/2 1/8" WITH "NOT" LOGIC ELEMENTS
22	900.32.6	SIGNAL AMPLIFIER
23	900.14.7	PROGRESSIVE START-UP VALVE G1/4"
24	900.18.8E	HIGH - LOW PESSURE DEVICE C/W M2
25	900.18.8P	HIGH - LOW PRESSURE DEVICE C/W PNEUMATIC CONTROL