

**1260.Ø.Stroke - 1261.Ø.Stroke**

Stroke / Ø	8	10	12	16	20	25	32	40	50
15	1260.8.15	1260.10.15	1260.12.15	1260.16.15	1260.20.15	1260.25.15	1260.32.15	1260.40.15	1260.50.15
25	1260.8.25	1260.10.25	1260.12.25	1260.16.25	1260.20.25	1260.25.25	1260.32.25	1260.40.25	1260.50.25
50	1260.8.50	1260.10.50	1260.12.50	1260.16.50	1260.20.50	1260.25.50	1260.32.50	1260.40.50	1260.50.50
75	1260.8.75	1260.10.75	1260.12.75	1260.16.75	1260.20.75	1260.25.75	1260.32.75	1260.40.75	1260.50.75
80	1260.8.80	1260.10.80	1260.12.80	1260.16.80	1260.20.80	1260.25.80	1260.32.80	1260.40.80	1260.50.80
100	1260.8.100	1260.10.100	1260.12.100	1260.16.100	1260.20.100	1260.25.100	1260.32.100	1260.40.100	1260.50.100
150			1260.12.150	1260.16.150	1260.20.150	1260.25.150	1260.32.150	1260.40.150	1260.50.150
160			1260.12.160	1260.16.160	1260.20.160	1260.25.160	1260.32.160	1260.40.160	1260.50.160
200			1260.12.200	1260.16.200	1260.20.200	1260.25.200	1260.32.200	1260.40.200	1260.50.200
250			1260.12.250	1260.16.250	1260.20.250	1260.25.250	1260.32.250	1260.40.250	1260.50.250
300			1260.12.300	1260.16.300	1260.20.300	1260.25.300	1260.32.300	1260.40.300	1260.50.300
320			1260.12.320	1260.16.320	1260.20.320	1260.25.320	1260.32.320	1260.40.320	1260.50.320
350					1260.20.350	1260.25.350	1260.32.350	1260.40.350	1260.50.350
400					1260.20.400	1260.25.400	1260.32.400	1260.40.400	1260.50.400
450						1260.25.450	1260.32.450	1260.40.450	1260.50.450
500						1260.25.500	1260.32.500	1260.40.500	1260.50.500

**MAGNETIC PISTON VERSION - 1260.Ø.Stroke.M ( BASE ) - 1261.Ø.Stroke.M**

Stroke / Ø	10	12	16	20	25	32	40	50
15	1261.10.15.M	1261.12.15.M	1261.16.15.M	1261.20.15.M	1261.25.15.M	1261.32.15.M	1261.40.15.M	1261.50.15.M
25	1261.10.25.M	1261.12.25.M	1261.16.25.M	1261.20.25.M	1261.25.25.M	1261.32.25.M	1261.40.25.M	1261.50.25.M
50	1261.10.50.M	1261.12.50.M	1261.16.50.M	1261.20.50.M	1261.25.50.M	1261.32.50.M	1261.40.50.M	1261.50.50.M
75	1261.10.75.M	1261.12.75.M	1261.16.75.M	1261.20.75.M	1261.25.75.M	1261.32.75.M	1261.40.75.M	1261.50.75.M
80	1261.10.80.M	1261.12.80.M	1261.16.80.M	1261.20.80.M	1261.25.80.M	1261.32.80.M	1261.40.80.M	1261.50.80.M
100	1261.10.100.M	1261.12.100.M	1261.16.100.M	1261.20.100.M	1261.25.100.M	1261.32.100.M	1261.40.100.M	1261.50.100.M
150		1261.12.150.M	1261.16.150.M	1261.20.150.M	1261.25.150.M	1261.32.150.M	1261.40.150.M	1261.50.150.M
160		1261.12.160.M	1261.16.160.M	1261.20.160.M	1261.25.160.M	1261.32.160.M	1261.40.160.M	1261.50.160.M
200		1261.12.200.M	1261.16.200.M	1261.20.200.M	1261.25.200.M	1261.32.200.M	1261.40.200.M	1261.50.200.M
250		1261.12.250.M	1261.16.250.M	1261.20.250.M	1261.25.250.M	1261.32.250.M	1261.40.250.M	1261.50.250.M
300		1261.12.300.M	1261.16.300.M	1261.20.300.M	1261.25.300.M	1261.32.300.M	1261.40.300.M	1261.50.300.M
320		1261.12.320.M	1261.16.320.M	1261.20.320.M	1261.25.320.M	1261.32.320.M	1261.40.320.M	1261.50.320.M
350				1261.20.350.M	1261.25.350.M	1261.32.350.M	1261.40.350.M	1261.50.350.M
400				1261.20.400.M	1261.25.400.M	1261.32.400.M	1261.40.400.M	1261.50.400.M
450					1261.25.450.M	1261.32.450.M	1261.40.450.M	1261.50.450.M
500					1261.25.500.M	1261.32.500.M	1261.40.500.M	1261.50.500.M

**NON ROTATING HEXAGONAL ROD VERSION- 1260.Ø.Stroke.E (BASE)-1261.Ø.Stroke.E**

Stroke/Diam.	12	16	20	25	32	40	50
15	1261.12.15.E	1261.16.15.E	1261.20.15.E	1261.25.15.E	1261.32.15.E	1261.40.15.E	1261.50.15.E
25	1261.12.25.E	1261.16.25.E	1261.20.25.E	1261.25.25.E	1261.32.25.E	1261.40.25.E	1261.50.25.E

50	1261.12.50.E	1261.16.50.E	1261.20.50.E	1261.25.50.E	1261.32.50.E	1261.40.50.E	1261.50.50.E
75	1261.12.75.E	1261.16.75.E	1261.20.75.E	1261.25.75.E	1261.32.75.E	1261.40.75.E	1261.50.75.E
100	1261.12.100.E	1261.16.100.E	1261.20.100.E	1261.25.100.E	1261.32.100.E	1261.40.100.E	1261.50.100.E
150	1261.12.150.E	1261.16.150.E	1261.20.150.E	1261.25.150.E	1261.32.150.E	1261.40.150.E	1261.50.150.E
200	1261.12.200.E	1261.16.200.E	1261.20.200.E	1261.25.200.E	1261.32.200.E	1261.40.200.E	1261.50.200.E
250	1261.12.250.E	1261.16.250.E	1261.20.250.E	1261.25.250.E	1261.32.250.E	1261.40.250.E	1261.50.250.E
300	1261.12.300.E	1261.16.300.E	1261.20.300.E	1261.25.300.E	1261.32.300.E	1261.40.300.E	1261.50.300.E
350			1261.20.350.E	1261.25.350.E	1261.32.350.E	1261.40.350.E	1261.50.350.E
400			1261.20.400.E	1261.25.400.E	1261.32.400.E	1261.40.400.E	1261.50.400.E
450				1261.25.450.E	1261.32.450.E	1261.40.450.E	1261.50.450.E
500				1261.25.500.E	1261.32.500.E	1261.40.500.E	1261.50.500.E

Code	Description	8	10	12	16	20	25	32	40	50
1200.Ø.01	Foot	1260.8.01	1260.10.01	1260.12.01	1260.16.01	1260.20.01	1260.25.01	1260.32.01	1260.40.01	1260.50.01
1200.Ø.02	Flange	1260.8.02	1260.10.02	1260.12.02	1260.16.02	1260.20.02	1260.25.02	1260.32.02	1260.40.02	1260.50.02
1200.Ø.03	Rear eye	1260.8.03	1260.10.03	1260.12.03	1260.16.03	1260.20.03	1260.25.03	1260.32.03	1260.40.03	1260.50.03
1200.Ø.04	Rod fork (pin)	1260.8.04	1260.10.04	1260.12.04	1260.16.04	1260.20.04	1260.25.04	1260.32.04	1260.40.04	1260.50.04
1200.Ø.04/1	Rod fork (clips)	1260.8.04/1	1260.10.04/1	1260.12.04/1	1260.16.04/1	1260.20.04/1	1260.25.04/1	1260.32.04/1	1260.40.04/1	1260.50.04/1
1200.Ø.05	Endcap nut	1260.8.05	1260.10.05	1260.12.05	1260.16.05	1260.20.05	1260.25.05	1260.32.05	1260.40.05	1260.50.05

**LINEAR CONTROL UNITS - ord. code: 1260.Ø.stroke.GLB**

Ø/stroke	100	150	200	250
20	1260.20.100.GLB	1260.20.150..GLB	1260.20.200..GLB	-
25	1260.25.100.GLB	1260.25.150..GLB	1260.25.200..GLB	1260.25.250.GLB

1260.12.51BS	PISTON ROD LOCK C/W MOUNTING BRACKET FOR MICROCYLINDERS Ø 12 AND Ø 16
1260.20.51BS	PISTON ROD LOCK C/W MOUNTING BRACKET FOR MICROCYLINDERS Ø 20
1260.25.51BS	PISTON ROD LOCK C/W MOUNTING BRACKET FOR MICROCYLINDERS Ø 25
1260.12.51B	PISTON ROD LOCK FOR MICROCYLINDERS Ø 12 AND Ø 16
1260.20.51B	PISTON ROD LOCK FOR MICROCYLINDERS Ø 20
1260.25.51B	PISTON ROD LOCK FOR MICROCYLINDERS Ø 25

**PISTON ROD LOCK MOUNTING BRACKET**

1260.12.51S	PISTON ROD LOCK MOUNTING BRACKET FOR MICROCYLINDERS Ø 12 AND Ø 16
1260.20.51S	PISTON ROD LOCK MOUNTING BRACKET FOR MICROCYLINDERS Ø 20
1260.25.51S	PISTON ROD LOCK MOUNTING BRACKET FOR MICROCYLINDERS Ø 25

1260.Ø.F	SENSOR CLAMPS
1213.6.5	Microcylinder Ø 6 Stroke 5
1213.6.10	Microcylinder Ø 6 Stroke 10
1213.6.20	Microcylinder Ø 6 Stroke 20
1213.8.5	Microcylinder Ø 8 Stroke 5
1213.10.3	Microcylinder Ø 10 Stroke 3
1213.10.5	Microcylinder Ø 10 Stroke 5
1213.10.10	Microcylinder Ø 10 Stroke 10
1273.4.10	Microcylinder Ø 4 stroke 10 - simple acting front spring